




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H01H 23/08, 1/58, 1/40, 21/12		A1	(11) International Publication Number: WO 95/00963
			(43) International Publication Date: 5 January 1995 (05.01.95)
(21) International Application Number: PCT/US94/05120 (22) International Filing Date: 9 May 1994 (09.05.94) (30) Priority Data: 08/083,017 25 June 1993 (25.06.93) US (71) Applicant: UNITED TECHNOLOGIES AUTOMOTIVE, INC. [US/US]; 5200 Auto Club Drive, Dearborn, MI 48126 (US). (72) Inventors: KRUPP, Eric, J.; 7695 Ridge Road, Canton, MI 48187 (US). BENZIE, Thomas, P.; 44508 Penney Court, Canton, MI 48187 (US). (74) Agents: HOFER, Ronald, L. et al.; Harness, Dickey & Pierce, P.O. Box 828, Bloomfield Hills, MI 48303 (US).			(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: **POWER WINDOW SWITCH CONTROL APPARATUS**

(57) Abstract

A power switch control module (100) for a power window control circuit of a motor vehicle. The control module incorporates a printed circuit board (102), a plurality of switch contacts (104a-104f) secured to the printed circuit board (102), a plurality of connector terminals (108a-108e) also secured to the printed circuit board (102), a plurality of high current traces (110a-110e) formed on an upper surface (106) of the printed circuit board (102) for coupling selected pairs of the switch contacts and connector terminals electrically together, and a switch control (112). The switch control (112) is mounted in a frame member (114) for pivotal movement relative to the printed circuit board (102) and is movable between up and down positions. When in the up position the switch control (112) electrically couples a first selected pair of switch contacts (104a-104f) and when in the down position the switch control (112) electrically couples a second selected pair of the switch contacts (104a-104f). The high current traces (110a-110e) are capable of handling about 20-80 amps of current. Since they are formed on the upper surface (106) of the printed circuit board (102), no injection molding, tooling or techniques are required for construction of the module (100) as typically required with prior art control modules. Also, the undersurface of the printed circuit board (102) can advantageously be used to mount other electronic components of the control circuit.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

POWER WINDOW SWITCH CONTROL APPARATUS

FIELD OF THE INVENTION

This invention relates to electrical switching assemblies, and more particularly to a power control switching circuit for high current switching. The power control
5 switching circuit is particularly well adapted for use with power window control circuits in motor vehicles which utilize power driven window assemblies.

BACKGROUND OF THE INVENTION

Power windows are now commonly offered in many motor vehicles such as automobiles and trucks. Such power windows usually incorporate at least one DC
10 motor for driving the window up and down in response to an operator actuatable switch. The current required to drive such motors is usually fairly high, and most often well above that which would ordinarily be capable of being transmitted by printed circuit boards. As is well known, conventional printed circuit boards have traditionally been limited to low current applications where currents are kept
15 generally below about 0.5 amps. The current typically required for driving motors associated with power window control circuits is generally ranges from about 20 to 80 amps.

Heretofore, the standard approach to automotive switch control design has involved insert molding technology. This involves using a plurality of independent
20 brass or copper lead frames (i.e., conductors) to carry high electrical current between a vehicle wiring harness and the switch contacts of an operator accessible switch control. These lead frames are typically imbedded in a plastic body or substrate. This process generally requires specialized injection mold tooling and techniques which can accommodate variously shaped and sized lead frames.
25 Frequently, "two shot" molding is required in which the plastic material above and below the portions of the lead frame is injected into the mold in sequential steps. Such apparatus and procedures are relatively expensive and time consuming and add to the complexity and cost of power window control circuits in view of the increased tooling expense required to produce such assemblies. Also, the plastic
30 body portion described above is typically restricted to accommodating only the lead frames and associated switch contacts. Thus, a separate printed circuit board is typically needed for the electronic components of the control circuit. This also significantly increases the overall cost of the control circuit.

- 2 -

Accordingly, it is the principal object of the present invention to provide a power switching control module which can be used with a conventional printed circuit board to enable high current switching for use in power window control circuits and automotive vehicles.

5 It is still another object of the present invention to provide a power switching control module in which high current traces are employed on the surface of a printed circuit board in lieu of imbedding a portion of a lead frame within an independent plastic body piece, to thereby eliminate the need for injection molding tooling and techniques.

10 SUMMARY OF THE INVENTION

The above and other objects are accomplished by a power switching control module in accordance with preferred embodiments of the present invention.

In one preferred embodiment the module includes a printed circuit board, a plurality of switch contacts secured to the printed circuit board, a plurality of connector terminals secured to the printed circuit board, a plurality of high current traces formed on an outer surface of the printed circuit board for coupling selected ones of the switch contacts and connector terminals electrically together, and an operator actuatable switch control movable between an up and a down position which includes a pair of activating elements therein, where at least one of the activating elements causes a first conductive member to couple selected ones of the switch contacts together electrically when the switch control is in the up position, and where at least one of the activating elements causes a second conductive member to couple at least a second pair of switch contacts electrically together. In the preferred embodiment a frame member is also associated with the printed circuit board and pivotally mounts the switch control such that the switch control may be moved pivotally between the up and down positions.

In the preferred embodiments the high current traces are preferably formed from copper and are capable of carrying from between about 20 amps to 80 amps. The connector terminals are further connectable to a wiring harness of a vehicle having a conventional terminal connector. Thus, current can be transmitted between the vehicle wiring harness and the connector terminals and controlled by the switch control.

- 3 -

BRIEF DESCRIPTION OF THE DRAWINGS

The various advantages of the present invention will become apparent to one skilled in the art by reading the following specification and subjoined claims and by referencing the following drawings in which:

5 Figure 1 is an illustration of a typical prior art switching control assembly incorporating a plurality of lead frames imbedded in a plastic component via injection molding techniques;

 Figure 2 is an exploded perspective view of a power switching control module in accordance with a preferred embodiment of the present invention showing the
10 high current traces formed on an outer surface of the printed circuit board thereof.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figure 1, there is shown a typical prior art switching control module 10. The switching control module 10 incorporates a plastic body portion 12 within which are imbedded portions of a plurality of lead frames 14 and portions of
15 a plurality of switch contacts 16. A plurality of additional lead frames 15 may also be included for supporting a separate printed circuit board 10a. The module 10 is constructed with injection molding tooling and techniques. This involves placing portions of the lead frames and portions of the switch contacts within the mold before injecting the material which will form the plastic body portion 12. Since lead
20 frames having a variety of shapes and sizes are often required in producing switching control modules for a variety of vehicles, changes in injection molding tooling can add significantly to the expense of producing the switching control module 10. Even without tooling changes, the equipment required to injection mold the plastic body portion 12 and the steps required to perform injection molding still
25 represent a significant added expense in producing the module 10. Still further, a separate printed circuit board is required to hold the electronic components of the control circuit with which the module 10 is used. This further increases the overall cost of the control circuit.

Referring now to Figure 2, there is shown a power switching control module
30 100 in accordance with a preferred embodiment of the present invention. The module 100 generally comprises a printed circuit board 102, a plurality of switch contacts 104a-104f secured to an upper surface 106 of the printed circuit board 102, a plurality of connector terminals 108a-108e secured to the printed circuit board 102, a plurality of high current traces 110a-110e formed on the upper surface 106 of the

- 4 -

printed circuit board 102, and a switch control 112. In the preferred embodiment the switch control 112 is pivotally coupled to a frame member 114 via a plurality of shoulder portions 116 which are mountable within a pair of apertures 118 in arm portions 120 of the frame member 114.

5 The switch control 112 is known in the art and generally includes at least a pair of switch activating elements 122a and 122b therein which are partially housed within a recess in a lower portion 112a. Each of the elements 122a and 122b are biased outwardly of the lower portion 112a by a pair of springs 125a and 125b. The switch control 112, when secured to the frame member 114, is movable pivotally
10 between an up position and a down position. This is accomplished by the operator either pulling up or pushing down on a portion 124 of the switch control 112 with the fingers of a hand. The frame member 114 is further adapted to be secured in any conventional fashion to the printed circuit board 106 such that the activating elements 122a, 122b of the switch control 112 are positioned over the switch
15 contacts 104a-104f. The frame member 114 is also preferably constructed from plastic such as by molding.

With further reference to Figure 2, the connector terminals 108 are adapted to be coupled to a terminal connector 126 of a vehicle wiring harness 128. The terminal connector 126 includes contacts therein, in conventional fashion, which
20 couple a plurality of conductors 130 of the wiring harness 128 to corresponding ones of the connector terminals 108 when the terminal connector 126 is physically inserted over the connector terminals 108.

In the preferred embodiment, the power switching control module 100 incorporates a pair of conductive elements 132a and 132b which are adapted to be
25 placed over the switch contacts 104c and 104d on the printed circuit board 102. It will be noted that switch contacts 104c and 104d are each shaped in the form of a "Y". The conductive element 132a sits on the switch contact 104c and "rocks" into contact with one or the other of the switch contacts 104a or 104e. Similarly, the conductive element 132b rests on the switch contact 104d and rocks into contact
30 with either the switch contact 104f or 104b. The switch contacts 104c and 104d are further positioned such that they sit on opposite sides of a center-line extending between the shoulder portions 116.

In operation, when the switch control 112 is not engaged (i.e., in a "neutral" position) the conductive element 132a is biased by its associated spring 125a and
35 activating element 122a into contact with, for example, switch contact 104a. Thus,

- 5 -

a complete current path exists between contacts 104c, 104a, connector terminal 108c and terminal 108a. The other conductive element 132b is biased, for example, into contact with switch contact 104f. Thus, a complete current path is formed between contacts 104f and 104d, and terminals 108a and 108d. When an operator
5 pushes the portion 124 of the switch control 112 upwardly, the activating element 122a "rocks" the conductive element 132a so that it electrically connects switch contacts 104c and 104e, thus forming a first circuit. When the switch control is pushed downwardly from its center (i.e., neutral) position by the operator, it moves pivotally relative to the printed circuit board 102 and the activating element 122b
10 urges the conductive element 132 to "rock" into electrical contact with the switch contact 104d. When switch contacts 104b and 104d are electrically coupled together, a current path is formed between connector terminals 108d and 108b, thus forming a second circuit. Current flowing in the circuit paths formed in the up and down positions of the switch control 112 may thus be used to control a reversible DC
15 motor of a power window control circuit such that the motor causes a window to be raised while the switch control 112 is held by the operator in the position, or lowered when the switch control 112 is held in the down position.

The high current traces 110a-110d each are formed preferably of copper deposited on the upper surfaces 106 of the printed circuit board 102 and are each
20 adapted to carry about 20-80 amps of current. Other suitable conductive material could also be used in lieu of copper. Most importantly, however, the use of the high current traces 110a-110d allows the power control module 100 to be constructed in accordance with more conventional printed circuit board construction techniques and without the need for any injection molding tooling or techniques to be applied in
25 constructing the module 100. Furthermore, the electronic components of the control circuit can be mounted on the opposite side 106a of the printed circuit board if so desired. This can help to significantly reduce the overall cost of the control circuit within which the module 100 is used.

The power control module 100 thus provides a relatively inexpensively
30 constructed power switching module for controlling the high current switching needed to operate a power window control circuit. While the invention 100 has been described in connection with a power window control circuit for a vehicle, it will be readily appreciated that the power switching control module 100 could readily be employed in a wide variety of other high current switching circuits to significantly
35 reduce the cost of such circuits. For example, the switching control apparatus

- 6 -

described herein could readily be adapted for use, with little or no modification to control the power seat(s) of a vehicle, a power rear view mirror, vehicle lighting, vehicle heating and cooling circuits, or a rear window defroster. It will also be appreciated that the apparatus 100 of the present invention is readily adaptable to
5 a wide variety of applications other than those in connection with motor vehicles.

Those skilled in the art can now appreciate from the foregoing description that the broad teachings of the present invention can be implemented in a variety of forms. Therefore, while this invention has been described in connection with particular examples thereof, the true scope of the invention should not be so limited
10 since other modifications will become apparent to the skilled practitioner upon a study of the drawings, specification and following claims.

- 7 -

WE CLAIM:

1. A switch control apparatus for high current switching, said apparatus comprising:
 - a printed circuit board;
 - 5 a plurality of switch contacts mechanically coupled to said printed circuit board;
 - a plurality of connector terminals physically coupled to said printed circuit board;
 - a plurality of high current traces formed on an outer surface of said printed circuit board, said high current traces each coupling at least one of said switch contacts with at least one of said connector terminals, said high current traces being operable to handle a current in the range of about 20 amps to 80 amps;
 - 10 an operator actuatable switch control for controllably electrically coupling at least one selected pair of said switch contacts, whereby moving said switch control to a closed position causes at least a pair of said connector terminals to be electrically coupled.
2. The apparatus of claim 1, further comprising a wiring harness having a connector, said connector being operable to electrically couple with said connector terminals to allow electrical current to be transmitted between said wiring harness and said connector terminals.
- 20 3. The apparatus of claim 1, further comprising frame means for mounting said switch control such that said switch control is movable rotatably between said up and said down positions.

- 8 -

4. A power window switch control apparatus for switching of high current signals in a power window control circuit of a vehicle, said apparatus comprising:
- a printed circuit board;
 - a plurality of switch contacts mechanically seated within said printed
 - 5 circuit board;
 - a plurality of high current connector terminals mechanically seated within said printed circuit board;
 - a plurality of copper traces formed on an outer surface of said printed circuit board, said copper traces being operable to handle current within a range of
 - 10 about 20-80 amps, each of said high current traces coupling at least one of said switch contacts and at least one of said high current connector terminals electrically together;
 - an operator actuatable switch control having a plurality of activating elements and movable pivotally between an up position and a down position, said
 - 15 switch control coupling at least a first selected pair of said switch contacts when in said up position and at least a selected second pair of said switch contacts when moved into said down position, to thereby enable current flow between a selected first pair of connector terminals when said switch control is in said up position and current flow between a selected second pair of connector terminals when said switch
 - 20 control is in said down position.
5. The apparatus of claim 4, further comprising:
- a vehicle wiring harness; and
 - an electrical connector electrically coupled to said vehicle wiring harness, said electrical connector being electrically connectable to said connector
 - 25 terminals such that current can be transmitted between at least one of said first and said second selected pairs of connector terminals.

- 9 -


6. A power window switch control apparatus for switching current in the range of about 20 amps to 80 amps to elevationally control placement of a vehicle window, said apparatus comprising:


- a printed circuit board having an outer surface;
- 5 a plurality of switch contacts secured to said printed circuit board;
- a plurality of connector terminals secured to said printed circuit board;
- a plurality of high current copper traces formed on said upper surface of said printed circuit board, each of said copper traces coupling a selected one of said switch contacts and a selected one of said connector terminals electrically
- 10 together;
- a frame secured to said printed circuit board, said frame having a pair of outwardly protruding arm portions each having an aperture therethrough;
- a first conductive element and a second conductive element; and
- a switch control movable pivotally by an operator between an up
- 15 position and a down position, said switch control including a plurality of activating elements, said switch control causing a first selected pair of said switch contacts to be electrically coupled together via said first conductive element when said switch control is in said up position and causing a selected second pair of said switch contacts to be electrically coupled together via said second conductive element when
- 20 said switch control is moved pivotally into said down position.

7. The apparatus of claim 6, further comprising:

- a vehicle wiring harness having a plurality of conductors; and
- an electrical connector electrically coupled to said plurality of
- conductors for electrically coupling said plurality of conductors to said connector
- 25 terminals, said terminal connector operating to transmit electrical current between said connector terminals and said terminal connector.

1/2





INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 94/05120

A. CLASSIFICATION OF SUBJECT MATTER

IPC 5

H01H23/08

H01H1/58

H01H1/40

H01H21/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5

H01H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR,A,2 262 474 (CITROEN) 19 September 1975 see page 2, line 27 - page 3, line 25; figures 1-3 ---	1
A	DE,A,32 41 159 (FA. GEORG SCHLEGEL) 10 May 1984 see page 3, paragraph 3; claim 1; figures ---	1
A	GB,A,2 180 415 (YAZAKI CORP.) 25 March 1987 see abstract; figures ---	2
A	DE,U,92 12 458 (SWF AUTO-ELECTRIC) 21 January 1993 see page 3, last paragraph; figures -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 September 1994

Date of mailing of the international search report

05.10.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Janssens De Vroom, P

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. International Application No

PCT/US 94/05120

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2262474	19-09-75	NONE	
DE-A-3241159	10-05-84	DE-A- 3335275 US-A- 4590342	18-04-85 20-05-86
GB-A-2180415	25-03-87	JP-B- 3043100 JP-A- 62061856 DE-A- 3630816 US-A- 4703397	01-07-91 18-03-87 19-03-87 27-10-87
DE-U-9212458	21-01-93	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.